SAFETY DATA SHEET

Issued Date 2010/6/28
Revision Date 2022/10/12

1. Identification

* Product name Stained Hobby Green

* Reference number 21213

* Company Washin Paint Co.,Ltd.

* Company address 2100-18 Kamiyoshiba Satte-shi Saitama-ken 340-0121 Japan

* Section concerned Engineering Department

* Person in change Takeyuki Kawashima

* Phone No. 0480-48-2021

* FAX No. 0480-48-2024

* Emergency contact 0480-48-2021

* Product kind Water-soluble resin paint

* Principal use Hobby paint

2. Hazards identification

[Classification]

Usesude	Category	Signal word			
Hazards	Hazard statement				
Flammable liquida	Category 2	Danger			
Flammable liquids	Highly flammable liquid and vapour.				
Acute tessicity Oral	Not classified				
Acute toxicity Oral		·			
A sorte de cisita a December	Not classified				
Acute toxicity Dermal		•			
Acute texicity Cooce	Not applicable				
Acute toxicity Gasas		•			
Acute texicity Venevus	Not classified				
Acute toxicity Vapours		·			
A	Not classified				
Acute toxicity Mists					
01:	Not classified				
Skin corrosion/irritation		-			
	Category 2	Warning			
Serious eye damage/eye irritation	Causes serious eye irritation.				
	Category 1	Danger			
Respiratory sensitization	May cause allergy or asthma symptoms or breathing difficulties if inhaled.				
	Category 1	Warning			
Skin sensitization	May cause an allergic skin reaction.				
	Not classified				
Germ cell mutagenicity					
	Not classified				
Carcinogenicity					
	Category 2	Warning			
Reproductive toxicity	Suspected of damaging fertility or the				
Specific target organ systemic toxicity	Category 1	Danger			
Single exposure	Causes damage to organs or state a				
Specific target organ systemic toxicity	Category 1	Danger			
Repeated exposure		ted, if known through prolonged or repeated exposure.			
	Not classified				
Aspiration hazard	NOT Classified				
Hazardous to aquatic environment	Not classified				
Acute		1			
Hazardous to aquatic environment	Not classified				
Chronic					
	Classification not possible				
Hazardous to the ozone layer	2.335maddon nac passible	I			
* If the signal would "Danger" applie	s the signal word "Worning" should not	annoar			

^{*} If the signal word "Danger" applies, the signal word "Worning" should not appear.

^{*} For the details with "Specific target organ systemic toxicity", refer to "11.Toxicological information".

[Symbol]

Flame











[Precautionary statement]

(Prevention)

- * Obtain and understand special instructions before use.
- * Keep away from ignition sources such as heat/sparks/open flame. No smoking.
- * Store container tightly and avoid release to the environment.
- * Prevent the electro static discharge. Ground a container/carrier receptacle and so on.
- * Use the tools that sparks don't come out.
- * Avoid breathing vapours/mist/spray.
- * Don't eat, drink or smoke when using this product.
- * Wear protective gloves and eye/face protection when it needs.
- * Wash hands thoroughly and gargle after handling.

(Response)

- * In case of fire, use carbon dioxide/powder/foams for extinction.
- * If inhaled: Remove to fresh air and keep at rest in a position comfortable for breathing. Seek medical advice/attention if you feel unwell.
- * If in eyes: Rince cautiously with water, get medical advice/attention.
- * If on skin or cloth: Wash with plenty of soap and water. Take off contaminated clothing and exchange it.
- * If skin irritation occurs, seek medical advice/attention.
- * If exposed or concerned: Get medical attention/advice.

(Strage)

* Store container tightly closed in the place which well-ventilated, cool and child doesn't reach.

(Disposal)

- * Don't dispose contents to the river and the sewage. Dispose after using them up.
- * Dispose container in accordance with local/regional/national regulation. Don't use another purpose.

3. Composition/information on ingradients

Property Mixture

Product kind Water-soluble resin paint

Chemical name	Weight (%)	CAS No.	Chemical structure	Notice duty
2-ethoxyethanol	0.22	110-80-5	C4H10O2	0
chlomium	0.23	_	Cr	0
additive	0~1	_	_	_
1-propanol	1~5	71-23-8	С3Н7ОН	0
1-butanol	1~5	71-36-3	C4H9OH	0
ethanol	10~20	64-17-5	C2H5OH	0
water	20~30	7732-18-5	H2O	_
2-propanol	20~30	67-63-0	С3Н7ОН	0
resin	20~30	_	_	_
_	_	_	_	_

4. First-aid measures

(When swallowing)

- * Without making vomit by force, be rested and have a medical attention.
- * The vomit doesn't make swallow. Get medical attention.

(When inhaling)

- * Do the artificial respiration in case of breathing's being irregular or stopping.
- * The vomit doesn't make swallow.
- * Remove to fresh air and keep at rest in a position comfortable for breathing. Seek medical advice/attention if you feel unwell.

21213

(When adhering to the skin)

- * Wipes up quickly with cloth and washes it off sufficiently using plenty of water and soap.
 - Don't use organic solvent, thinner and so on.
- * If you get damage or feel pain, seek medical advice/attention.

(When entering eyes)

- * Wash for more than 15 minutes with a plenty of water at once.
- * Get a medical attention as fast as possible.

5. Fire-fighting measures

(Suitable extinguishing media)

* Water (), Carbon dioxide (O), Foams (O), Powder (O), Dry sand (), Other (),

(Specific hazards arising from the chemical)

* Liquid and vapour are extremely flammable.

If they expose to heat, flame and an oxidizer, there is danger of intense fire.

- * When heated, there is a fear of intense bust of container by expansion or resolution.
- * When burning, there is possibility to make carbon monoxide occur.

(Specific extinguishing method)

- * Tell Fire Service the place and the dangerous/hazardous property.
- * Prevent outflow being in water pipe or watercourse.
- * Wear respiratory-protective-equipment and protective-glove.
- * Remove combustibles quickly from the surrounding area.
- * Uses the suitable extinguishing media.
- * Do fire fighting from the windward.

(Special protective equipment and precautions for fire-fighters)

* Wear respiratory-protective-equipment, chemical-defense clothes/glove/boots,/glasses/mask as occasion demands.

6. Accidental release measures

(Personal precautions, protective equipment and emargency prosedures)

- * Lead personnel to the windward from outflow areas.
- * Avoid the inhalation of vapour. Avoid the contact to the skin and eyes. Promote ventilation.
- * Wear protective equipments (gloves, protective mask, apron and goggles).

(Environmental precautions)

- * Prevent outflow being in water pipe or watercourse.
- * When water pipe or watercourse are polluted, contact organs concerned.

(Methods and materials for containment and cleaning up)

- * Remove ignition sources. Prohibit smoking and fire. Use the tools which don't spark.
- * Collects outflow to the container which can be shut, and move it to the safe place.
- * Prevent outflow using dry sand, earth or other imcombustible material, and make absorb residue to collect it.
- * It may use water sprayer to absorb the diffusion of vapour.
- * Dispose wastes based on the regurations concerned.

7. Handling and storage

(Handring: Technical measure)

- * Handle this based on the related laws (Industrial Safety and Health Law, Fire Defense Law, etc.).
- * Forrow the operation-standard, keep working atmosphere below TLV, promote ventilation.
- * When in working, wear antistatic work clothing, shoes.
- * Remove ignition sources, prohibit smoking and fire, Use tools which don't spark.
- * Ground equipments (transport, dip, stirring liquid) and use explosion-proof type electric equipments.
- * After handling, wash hands with soap water. It should wash work clothing separately.

(Handring: Notice)

- * Ground equipments and use explosion-proof type electric equipments.
- * Avoid contact with strong oxidizing reagent.
- * It has a fear of causing a reaction by heating, acidic material and alkaline material.
- * Use the container which has no damage, no corrosion and no breakage.
- * Gather used containers to the decided safekeeping place.

(Storage)

- * Store container tightly closed in the place which well-ventilated and cool.
- * Follow the Fire Defense Law and so on because of flammable liquid.

21213

8. Exposure controls/personal protection

Standard control concentration, threshold limit value etc.

(Control parameters e.g. occupational exposure limit values or biological limit values)

Chemical name	Standard control concentration	Tthreshold limit value	ACGIH (TLV)	PRTR
2-ethoxyethanol	5ppm	5ppm	5ppm	Class 1-57
chlomium	_	0.5mg/m3•Cr	0.5mg/m3	Class 1-87
additive	_	_	_	_
1-propanol	_	_	100ppm	_
1-butanol	25ppm	50ppm	20ppm	_
ethanol	_	_	1000ppm	_
water	_	_	_	_
2-propanol	200ppm	400ppm	200ppm	_
resin	_	_	_	_
_	_	_	_	_

[Equipment measure]

- * Set up sealed systems or local ventilation systems.
- * Set up safe shower, bathroom and face washing near the work area, and display the position.
- * Show the signs such like 'INFRAMABLES' or 'NO UNAUTHORIZED ENTRY'.
- * When handling flammable liquid, there needs explosion-proof type ventilation equipments/systems.

(Protection measure)

- * As occasion demands, wear following guards appropriately.
 - air-supplied respirator, air SCBA, oxygen SCBA, chemical-cartridge respirator, protective glasses, protective gloves, protective boots, protective clothing,
- * Check protective equipments regularly by the check list.
- * Don't eat, drink or smoke when using this product.
- * Wash hands with soap before eat, drink or smoke.
- * The person who showed the symptom of the asthma once should not contact this chemical because he may cause the same symptom.
- * Contact lens bring about special harm.
- Don't use soft contact lens because it absorbs irritant and has possibility to concentrate them.
- * Wear chemical-proof type protective gloves and antistatic protective shoes.

9. Physical and chemical properties

(Physical state: Liquid)

Colour	Indicate in the pr	oduct name	Density	0.93	$g/mL(25^{\circ}C)$	Flash point	18	°C
Odour	Solvent odour		PH	Not corre	spond	Ignition point	363	°C
Boiling point Low	ver 78.5	°C	Solbility	Sol. In wa	iter	Flammability or exp	losive limit	s
Boiling point Upp	er 100	°C	Partiton coef	fficient n-oc	tanol/water	Lower	2	%
Vapour pressur	re 7891	Pa (ref.)		No data		Upper	19	%

10. Stability and reactivity

(Chemical stability)

- * The product seems to be stable.
- * It has a possibility of the dangerous/harmful reaction.
- * It reacts to the oxidizing materials.
- * No other reactions were informed.

(Conditions to avoid)

- * Heating, Contact with the avoidance, Ignition source.
- * Degradation product which has dangerous/hazardous property.
- * Vapour of organic solvent.
- * Heat, light, metal powder and peroxide.

11. Toxicological information

Chemical name	Acute toxicity	Acute toxicity				
Gnemical name	Oral	Dermal Gasas	Vapours			
2-ethoxyethanol	Not classified	Not classified	Not applicable	Category 4		
chlomium	Classification not possible	Classification not possible	Not applicable	Classification not possible		
additive	Classification not possible	Classification not possible	Not applicable	Classification not possible		
1-propanol	Not classified	Not classified	Not applicable	Classification not possible		
1-butanol	Not classified	Not classified	Not applicable	Classification not possible		
ethanol	Not classified	Not classified	Not applicable	Not classified		
water	Not classified	Not classified	Not applicable	Not classified		
2-propanol	Not classified	Not classified	Not applicable	Not classified		
resin	Not classified	Not classified	Not applicable	Not classified		
_	-	-	_	-		

Chemical name	Acute toxicity	Skin corrosion/		Respiratory
Chemical hame	Mists	irritation	eye irritation	sensitization
2-ethoxyethanol	Classification not possible	Not classified	Category 2B	Classification not possible
chlomium	Classification not possible	Classification not possible	Category 2	Category 1A
additive	Classification not possible	Classification not possible	Classification not possible	Classification not possible
1-propanol	Classification not possible	Not classified	Category 1	Classification not possible
1-butanol	Classification not possible	Category 2	Category 2A	Classification not possible
ethanol	Classification not possible	Not classified	Category 2B	Classification not possible
water	Not classified	Not classified	Not classified	Not classified
2-propanol	Classification not possible	Not classified	Category 2	Classification not possible
resin	Not classified	Not classified	Not classified	Not classified
_	-	-	-	-

Chemical name	Skin sensitization	Germ cell mutagenicity	Carcinogenicity	Reproductive toxicity
2-ethoxyethanol	Not classified	Classification not possible	Classification not possible	Category 1B
chlomium	Category 1A	Classification not possible	Not classified	Classification not possible
additive	Classification not possible	Classification not possible	Classification not possible	Classification not possible
1-propanol	Classification not possible	Classification not possible	Not classified	Category 2
1-butanol	Classification not possible	Classification not possible	Classification not possible	Classification not possible
ethanol	Classification not possible	Classification not possible	Classification not possible	Classification not possible
water	Not classified	Not classified	Not classified	Not classified
2-propanol	Classification not possible	Classification not possible	Classification not possible	Category 2
resin	Not classified	Not classified	Not classified	Not classified
_	-	-	_	_

Chemical name	Specific target organ systemic	toxicity	Aspiration hazard	
Onemical name	Single exposure	Repeated exposure		
2-ethoxyethanol	Category 1	Category 1	Classification not possible	
chlomium	Category 3	Classification not possible	Classification not possible	
additive	Classification not possible	Classification not possible	Classification not possible	
1-propanol	Category 3	Classification not possible	Classification not possible	
1-butanol	Category 3	Category 1	Classification not possible	
ethanol	Category 3	Classification not possible	Classification not possible	
water	Not classified	Not classified	Not classified	
2-propanol	Category 1, 3	Category 1, 2	Classification not possible	
resin	Not classified	Not classified	Not classified	
_	_	_	_	

st Hazards information is peculiar to the chemicals. It doesn't change according to the content.

12. Ecological information

Chemical name	Hazardous to aquatic envi	zardous to aquatic environment			
Gnemical name	Acute	Chronic	Ozone layer		
2-ethoxyethanol	Not classified	Not classified	Classification not possible		
chlomium	Classification not possible	Classification not possible	Classification not possible		
additive	Classification not possible	Classification not possible	Classification not possible		
1-propanol	Not classified	Not classified	Classification not possible		
1-butanol	Not classified	Not classified	Classification not possible		
ethanol	Not classified	Not classified	Classification not possible		
water	Not classified	Not classified	Classification not possible		
2-propanol	Not classified	Not classified	Classification not possible		
resin	Not classified	Not classified	Classification not possible		
_	-	-	-		

* Hazards information is peculiar to the chemicals. It doesn't change according to the content.

* Residual property/resolvability

There are not data as a mixture.

* Creature accumulation characteristics

There are not data as a mixture.

There are not data as a mixture.

13. Disposal consideration

- * Requests disposal to the agency who has solid-waste-treatment license.
- * When disposing container, dispose after removing a content fully.
- * Dispose of contents/container in accordance with local/regional/national regulation.

14. Transport information

(National regulation)

* UN number 1263 * Guideline number 127

* Land transportation Follow the transporting way to be specified in the Industrial Safety and Health Law.

Fire Defense Law and so on.

* Air transportation Follow the transporting way to be specified in the Aviation Law.

* Marine transpotation Follow the transporting way to be specified in the Ship Safety Law.

* Fire Defense Law Annex class 4-1 Water-soluble Danger class II

(International regulation)

* UN number 1263 * UN proper shipping name PAINT

* UN classification Class 3 Flammable liquid

(Special precautions)

- * In case of transportation, carry "transportation notice" or "Yellow Card".
- * Confirm container tightly closed and no leaking before transportation.
- * In case of transportation, fix a container tightly and use buffering one as occasion demands.

15. Regulatory information

* Industrial Safety and Health Law

Dangerous goods Flammable liquid

Ordinance on the Prevention of Organic Solvent Poisoning
Class-2
Ordinance on Prevention of Lead Poisoning
Ordinance on Prevention of Hazards due to Specified Chemical Substances
Not applicable

* Pollutant Release and Transfer Register Law

* Poisonous and Deleterious Substances Control Law

Not applicable

* Fire Defense Law Annex class 4-1 Water-soluble

* Ship Safety Law Flammable liquid
* Offensive Odor Control Low Not listed

21213

16. Other information

(Main reference)

- * National Institute of Tecnology and Evaluation Opend data
- * Japan Paint Manufacturers Association

Raw material data base

The guide book for the creating SDS and label [mixture (paint)] Second edition Model MSDS and label samples [mixture (paint)]

* Japan Industrial Safety and Health Association

The OJT text for the MSDS of mixture (chemicals) by GHS compatible

- * "YOZAI Pocket Book"
- * "KIKEN BOSAI KYUKYU BINRAN"
- * International Chemical Safety Cards (ICSC)
- * SDS of raw materials

(Notice)

- * This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only.
- * It should not therefore be construed as guaranteeing any specific property of the product.
- * In case of use, set a safe conditions for handling.
- * All chemicals have possibility of unknown hazards, so it needs a due attention for handling.
- * Applicable scope of this document is only in Japan.